

SMARTen 24 STP Patch Panels

Features

SMARTen
WARRANTY

6A



- Support 24 ports per 1U
- High performance, supportable bandwidth up to 500MHz supporting IEEE 802.3an 10Gbps application
- Conform to ANSI/TIA/EIA-568-B.2-10, ISO/IEC 11801 2.1 edition and CENELEC EN50173 (200x) for Category 6A/CLASS E_A
- Special cap design for eliminating Alien Cross-Talk
- Simple labor-saving termination using standard Krone and 110 termination tools
- Excellent provisions for terminating shielded cables
- Enhanced cable retention fixture
- Sealed casing for superior EMI/RFI protection for shielded model panels
- Color coded wiring blocks, compatible with both T568A and T568B wiring options
- Backward compatible with Category 5e and Category 6 cabling standards
- Support solid and stranded 22-26 AWG wires
- Meets the transfer impedance standard requirement
- PatchView option only

SMARTen 24 STP Patch Panels

Description



SMARTen™

RiT SMARTen STP Patch Panels are part of the RiT SMARTen Cabling System™, featuring Category 6A performance. The system is designed to ANSI/TIA/EIA-568-B.2-10, ISO/IEC 11801 2.1 edition and CENELEC EN50173 (200x) for Category 6A/CLASS E_A.

The system is designed to support protocols running at up to IEEE 802.3an 10Gbps, 1000 Mbps, such as ATM 622 Mbps and Gigabit Ethernet.

PatchView™ Capability

Special SMARTen STP 24 Patch Panels models, when used in conjunction with RiT's PatchView Solution, are able to provide valuable connectivity information about the entire network to the PV4E management software.

LED indicators on panels identify any two ports patched together and enable 100% accurate Moves, Adds and Changes (MACs).

With its unique automated detection, LED-guided connection, and web-based remote maintenance capabilities, PV4E enables real-time, centralized management and troubleshooting for even the most dispersed networks.

SMARTen 24 STP Patch Panels

Description



The RiT SMARTen STP data communications patch panels meets the requirements for high-performance Category 6A networks for 10 Giga applications. The panels conform to ANSI/TIA/EIA-568-B.2-10, ISO/IEC 11801 2.1 edition and CENELEC EN50173 (200x) for Category 6A/CLASS E_A. The system is designed to support protocols running at up to IEEE 802.3an 10Gbps, 1000 Mbps, such as ATM 622 Mbps and Gigabit Ethernet and future high-speed applications.

The panels are optimized for ease of assembly and termination. With simple labor-saving termination using standard Krone & 110 Block termination tools and color-coded wiring blocks, installation costs are significantly reduced.

Special SMARTen STP models, when used in conjunction with RiT's PatchView system, are able to perform remote or on-site scanning of the patching configuration. The entire wiring center's patching configuration is continuously monitored by a scanner which reports the data to a remote terminal. The network administrator uses this data as a vital part of his cabling management system. The data may be displayed on the panel itself by LED indicators.

Servicing time is dramatically reduced as computerized LED displays guide the technician when performing Moves, Adds and Changes (MACs).

SMARTen 24 STP Patch Panels

Specifications



- **Front Interconnection (patch cord side)**
- 24 nine-position RJ-45 shielded modular jacks. Use of RiT SMARTen patch cords is recommended.
- **Back Interconnection (cables side)**
- 24 eight-position Krone & 110 tool-compatible blocks; accept 22 to 26 AWG wires, solid or stranded. Rated for up to a minimum of 200 re-termination

Note: Termination tools must be ordered separately.

- **Interconnection to RiT's PatchView system**

PVMax Panels – One 14-pin header on the back of the panel is used for connection to the PVMax Scanner.

Select Group B Scanner Attachment Cord according to the required length.

The scanning signal is transmitted over pin 9 of the RJ-45. Pin 9 exists in nine-position RJ-45 jack and plug designs, used for these patch panel models. A special patch cord - Jumper, including an extra wire and special RJ-45 plugs is needed. Please refer to the PatchView System and the Copper Cables and Cords sections for further details.

- **Indicators (in models adapted to PatchView only)**
- Port identification indicators - 24 red LEDs. Connected ports are identified by a pair of activated LEDs. A single port can be identified and the corresponding LED activated by a remote control command from the network management station.

SMARTen 24 STP Patch Panels - *Specifications*

Electrical Specifications

General

Height: 44.0 mm / 1.75" (1U)

Width: 482.6 mm / 19"

Depth: 100 mm

Weight: 1.3 Kg

Material

STEEL SAE 1020

Colors

Black background with gray silk screened markings

Environment

Temperature: -10 to 60°C

Humidity: 5-85% non-condensing

Compliance with International EMC Standards:

The SMARTen STP patch panel is designed to comply with EN-55022, Class B (Europe) and FCC Part 15, Subpart J, Class A (USA).